



315mm x 290mm



588mm x 475mm



950mm x 588mm



1190mm x 980mm



2380mm x 980mm

Please note graphics above are examples only. Customisation of the artwork is available for different provinces, regions or offices. Contact Ecoglo for more information.

Ecoglo S20 Evacuation Area Left signs are designed to be used in hazard zones to direct persons to safety. The signs will be clearly visible and readily understandable under all conditions of foreseeable use, including darkness.

#### SIGN DEFINITION

Evacuation area left from here.

#### PERFORMANCE

Ecoglo S20 Evacuation Area Left signs will absorb enough natural daylight to remain visible throughout the night.

Luminance – S20 grade signs easily exceed PSPA class G

UV Resistance – Loss of luminance after 1000 hrs ASTM G-155

Cycle 1 exposure: <10% Salt Spray Resistance – ASTM B117: Pass

Salt Spray Resistance – ASTM B117: Pass

Washability – ASTM D4828: Pass

Rate of Burning – ASTM D635: Pass

Surface Flammability – ASTM E162: Pass

Toxicity – Bombardier Toxic Gas Generation Test SMP800-C: Pass

Radioactivity – ASTM D3648: Pass

#### SUPPLY

The sign is available in sizes listed – see product order codes below.

PRODUCT CODE	PRODUCT NAME	SIGN DEFINITION	SIGN SIZE
S20-EAL315290	Evacuation Area Left	Evacuation area left from here	315mm x 290mm
S20-EAL588475	Evacuation Area Left	Evacuation area left from here	588mm x 475mm
S20-EAL950588	Evacuation Area Left	Evacuation area left from here	950mm x 588mm
S20-EAL1190980	Evacuation Area Left	Evacuation area left from here	1190mm x 980mm
S20-EAL2380980	Evacuation Area Left	Evacuation area left from here	2380mm x 980mm

#### COMPOSITION

The high visibility flat panel is manufactured from 5005 0.9mm aluminium sheet. Custom made photoluminescent pigments are embedded in thermoset polyester carriers to integrally bond the active ingredients onto the aluminium sheet following curing at high temperature – a process known as HTC.



This sign also has HTC Clear Coating added to protect the print in outdoor environments.

#### INSTALLATION

The sign should be installed using fixers (screws). Please note the sign is supplied without drill holes.

#### Contact

**Ecoglo International Limited**

Email: [info@ecoglo.com](mailto:info@ecoglo.com) Web: [www.ecoglo.com](http://www.ecoglo.com)