Product Data Sheet - Tsunami Evacuate Left TEL







Example only

Ecoglo S20 Tsunami Evacuate Left signs are designed to be used in tsunami hazard zones to direct persons to safety. The signs will be clearly visible and readily understandable under all conditions of foreseeable use, including darkness.

SIGN DEFINITION

Evacuate left from here

PERFORMANCE

Ecoglo S20 Tsunami Evacuate Left signs will absorb enough natural daylight to remain visible throughout the night.

Luminance – S20 grade signs easily exceed PSPA class G
UV Resistance – Loss of luminance after 1000 hrs ASTM G-155

Cycle 1 exposure: <10%

Salt Spray Resistance – ASTM B117: Pass

Washability – ASTM D4828: Pass Rate of Burning – ASTM D635: Pass

Surface Flammability – ASTM E162: Pass

Toxicity - Bombardier Toxic Gas Generation Test SMP800-C: Pass

Radioactivity - ASTM D3648: Pass

SUPPLY

The sign is available in one size only – see product order code below.

PRODUCT CODE	PRODUCT NAME	SIGN DEFINITION	SIGN SIZE
S20-TEL315155	Tsunami Evacuate Left	Evacuate Left From Here	315mm x 155mm

Please note graphics above are example only. Customisation of the artwork is available for different provinces, regions or offices. Contact Ecoglo for more information.

COMPOSITION

The high visibility flat panel is manufactured from 5005 0.9mm aluminium sheet. Custom made photoluminescent pigments are embedded in thermoset polyester carriers to integrally bond the active ingredients onto the aluminium sheet following curing at high temperature

- a process known as HTC.

This sign also has HTC Clear Coating added to protect the print in outdoor environments..

INSTALLATION

The sign should be installed using fixers (screws). Please note the sign is supplied without drill holes.

Contact

Ecoglo International Limited

Email: info@ecoglo.com Web: www.ecoglo.com