Product Data Sheet - Tsunami Evacuate Right TER







Example only

Ecoglo S20 Tsunami Evacuate Right signs are designed to be used in tsunami hazard zones to direct persons to safety. The signs will be clearly visible and readily understandable under all conditions of foreseeable use, including darkness.

SIGN DEFINITION

Evacuate right from here

PERFORMANCE

Ecoglo S20 Tsunami Evacuate Right signs will absorb enough natural daylight to remain visible throughout the night.

Luminance – S20 grade signs easily exceed PSPA class G UV Resistance – Loss of luminance after 1000 hrs ASTM G-155

Cycle 1 exposure: <10%

Salt Spray Resistance – ASTM B117: Pass

Washability – ASTM D4828: Pass

Rate of Burning - ASTM D635: Pass

Surface Flammability – ASTM E162: Pass

Toxicity - Bombardier Toxic Gas Generation Test SMP800-C: Pass

Radioactivity - ASTM D3648: Pass

SUPPLY

The sign is available in one size only – see product order code below.

PRODUCT CODE	PRODUCT NAME	SIGN DEFINITION	SIGN SIZE
S20-TER315155	Tsunami Evacuate Right	Evacuate Right From Here	315mm x 155mm

Please note graphics above are example only. Customisation of the artwork is available for different provinces, regions or offices. Contact Ecoglo for more information.

COMPOSITION

The high visibility flat panel is manufactured from 5005 0.9mm aluminium sheet. Custom made photoluminescent pigments are embedded in thermoset polyester carriers to integrally bond the active ingredients onto the aluminium sheet following curing at high temperature

- a process known as HTC.

This sign also has HTC Clear Coating added to protect the print in outdoor environments.

INSTALLATION

The sign should be installed using fixers (screws). Please note the sign is supplied without drill holes.

Contact

Ecoglo International Limited

Email: info@ecoglo.com Web: www.ecoglo.com